## BATTERY DATA SHEET





MF   MAINTENANCE FREE			
BATTERY		REF BIX30	L-BS
		6	
	AATERY		
			$\overline{\mathbf{h}}$
		4	
	4000.000 /	3	I.6Ah CAPACITY - Ah (20Hr)
Pb Pb months and back			30Ah CAPACITY - Ah (TOH)
			_
AGM construction (absorbed aci		DIME Length (A) :	NSIONS 166±2mm
• VRLA battery (Valve Regulated L	ead Acid)	Width (B) :	126±2mm
<ul><li>Supplied with a separate acid pa</li><li>Homologated by OEM</li></ul>	ck	Container height : Total height (C) :	173±2mm 173±2mm
FEAT	URES		
<ul><li>Upright installation only</li><li>Maintenance free (no water r</li></ul>	refilling)		
• Sealed after filling, no gas er	nission through venting		
<ul><li>hole (under normal operation)</li><li>High power</li></ul>			(C)
<ul><li>Does not need to be recharge</li><li>Suitable for cold weather</li></ul>	ed while stocked		
<ul><li>Reduction of plate sulfation</li><li>Higher life cycle (up to three</li></ul>	times longer than	126mm (B)	
conventional batteries) <ul> <li>Longer voltage hold</li> </ul>	5		166mm (A)
Longer voltage hold		TER	MINALS
UPGRAI	DE FOR		<mark>→</mark> 16.0 <del>→</del> mm
			9.0
WEIG			
Battery (with acid) :	Approx 9.56kg	FRONT	SIDE
	G ANGLE 20° 0° 10°	Rea	
25° 25°	20		
		38.1	
90 <u>°</u> Medium ir	0°90°	TOP	
			adaa@ha hattany aam
🖪 🖸 🖬 🛛 BS BATTER'	Y WWW.bs-	battery. <mark>com</mark>	sales@bs-battery.com