## BATTERY DATA SHEET



## LITHIUM BATTERY

### LITHIUM | ROBOT

# REF BSL-ST01



The BSL range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity Lithium cells, this range thus offers the robot great autonomy in working.

#### **FEATURES**

- Compatible battery type
- High cycle life: up to 500 cycles
- Long battery life: capacity sometimes higher than the original battery
- High quality Lithium cells (LG, Samsung, Panasonic,...)
- · More than 200 models of robots covered

#### **DIMENSIONS & WEIGHT**

 Length:
 147.8±1mm

 Width:
 92.8±1mm

 Height:
 64.5±2mm

 Weight:
 1.15kg (tolerance ±3%)

#### **APPLICATIONS**



#### COMPATIBILITY (LIST NOT EXHAUSTIVE)

- AMBROGIO
  TYPE L100 SERIE
- STIGA AUTOCLIP 140/325/520

25.2v VOLTAGE

219.24 ENERGY
Wh

8.7Ah CAPACITY

#### **SPECIFICATIONS**

Nominal voltage:	25.2V (18650 - 7S2P)
Energy:	219.24Wh
Nominal capacity:	8.7Ah
Technology:	Lithium-ion
Brand cells:	SAMSUNG - INR18650 - 29E
Protection function (PCM):	Over charge protection/Over discharge protection/Over current protection/Temperature protec- tion/Balanced function
Standard charge Max charge Current:	4.125A (29.4V max)
Standard discharge Standard discharge current: Max discharge current:	0.825A (cut-off voltage: 12.5V) 15A
Operationg temp. range Charge temperature: Discharge temperature: Storage temperature:	0°C to 45°C -10°C to 60°C 0°C to 40°C

#### **TERMINALS**

