

SLA
FACTORY ACTIVATED

SLA | READY TO START

REF **BTX12****12v**

VOLTAGE - V

180A

CCA - A (EN)

10.5Ah

CAPACITY - Ah (20Hr)

10Ah

CAPACITY - Ah (10Hr)

TECHNOLOGY

- Designed according to AGM technology (Absorbed acid)
- VRLA battery type
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Factory activated
- Environmentally friendly, spillproof design
- Multi-positional fitment
- Absolutely Maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Ready & Easy to use
- No acid handling - Very safe
- Increased power & Extended life
- Extreme vibration resistance

UPGRADE FOR


MF BTX12-BS

WEIGHT

Battery (with acid):


Approx 3.99kg

MOUNTING ANGLE



DIMENSIONS

| | |
|-------------------|------------|
| Length (A): | 150mm ±2mm |
| Width (B): | 87mm ±2mm |
| Container height: | 130mm ±2mm |
| Total height (C): | 130mm ±2mm |



TERMINALS (mm)

