

SLA
FACTORY ACTIVATED **MAX**

SLA MAX | PREMIUM QUALITY READY TO START

REF **BTX14HL****12v** VOLTAGE - v**220A** CCA - A (EN)**14.7Ah** CAPACITY - Ah (20Hr)**14Ah** CAPACITY - Ah (10Hr)

TECHNOLOGY

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES

- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe


UPGRADE FOR

MF BTX14L-BS
SLA BTX14L

WEIGHT


Battery (with acid): approx 4.60kg

MOUNTING ANGLE




DIMENSIONS

Length (A): 149mm ±2mm
Width (B): 87mm ±2mm
Container height: 144mm ±2mm
Total height (C): 144mm ±2mm




TERMINALS (mm)



FRONT



SIDE



TOP