

**SLA MAX**  
FACTORY ACTIVATED

SLA MAX | PREMIUM QUALITY READY TO START

REF

**BGZ16HL****12v****VOLTAGE - V****240A****CCA - A (EN)****16.8Ah****CAPACITY - Ah (20Hr)****16Ah****CAPACITY - Ah (10Hr)****TECHNOLOGY**

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

**FEATURES**


- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe

**UPGRADE FOR**


MF BTX14L-BS  
SLA BTX14L  
SLA MAX BTX14HL

**WEIGHT**

Battery (with acid): approx 5.48kg

**MOUNTING ANGLE****DIMENSIONS**

Length (A): 150mm ±2mm  
Width (B): 88.5mm ±2mm  
Container height: 145mm ±2mm  
Total height (C): 145mm ±2mm

**TERMINALS (mm)**