

SLA
FACTORY ACTIVATED **MAX**

SLA MAX | PREMIUM QUALITY READY TO START

REF **BGZ20H**

12V VOLTAGE - V

320A CCA - A (EN)

21.1Ah CAPACITY - Ah (20Hr)

20Ah CAPACITY - Ah (10Hr)

TECHNOLOGY

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES

- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe

UPGRADE FOR

 MF BTX20-BS
SLA BTX20

WEIGHT


Battery (with acid): approx 6.63kg

MOUNTING ANGLE



DIMENSIONS

Length (A): 176mm ±2mm
 Width (B): 89mm ±2mm
 Container height: 154mm ±2mm
 Total height (C): 154mm ±2mm



TERMINALS (mm)

