



Safety Data Sheet

Wet Flooded Lead-Acid Battery (Filled with Acid)

According to Regulation (EC) No 1272/2008
According to Regulation (EU) No 2020/878

Version :	4
Revision date :	18/04/2023

Section 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product Form: Article
Product name: Wet Flooded Lead-Acid Battery (Filled with Acid)
Product code : Lawn&Garden Ca/Ca battery
UFI code : N/A

1.2 Relevant identified uses of the substance and uses advised against:

1.2.1 Identified uses: Automotive, agricultural starter battery
1.2.2 Uses advised against: No additional information

1.3 Details of the supplier of the safety data sheet:

Supplier: **BS BATTERY SAS**
Address: 30 Rue Pasteur
92150 Suresnes
France
Telephone: (France) +33 1 83 62 45 55

1.4 Emergency telephone Number:

CHEMTREC (US, Canada & Mexico) 0086-1-800-424-9300
CHEMTREC (International) 0086-1-703-527-3887
Available outside office hours? YES NO

Section 2 Hazards Identification

2.1 Classification of the substance/mixture:

The mixture is classified as following according to REGULATION (EC) No 1272/2008:

Acute Tox. 4 (Oral)	H302
Skin corrosion/irritation Category 1A	H314
Eye irritation Category 1A	H318
Acute toxicity (inhalation:dust, mist) Category 1A	H332
Reproductive toxicity, Category 1A	H360Fd
Specific target organ toxicity (repeated exposure) Category 1A	H372
Hazardous to the aquatic environment -Acute Hazard, Category 1	H400
Hazardous to the aquatic environment - Chronic Hazard, Category 1	H410

For full text of H- phrases: see section 16



2.2 label elements:

Hazard Pictograms (CLP):



Signal Word (CLP):

Danger

Hazard Statement:

H314 - Causes severe skin burns and eye damage
H318 - Cause serious eye damage
H302+332 - Harmful if inhaled
H350 - May cause cancer (inhalation)
H360Fd - May damage fertility. Suspected of damaging the unborn child
H362 - May cause harm to breast-fed children
H372 - Causes damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statement:

P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P281 - Use personal protective equipment as required
P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313: IF exposed or concerned: Get medical advice/attention.
P310: Immediately call a POISON CENTER/doctor.

2.3 Other hazards:

Other hazards which do not result in classification: Lead may be toxic to blood, kidneys, central nervous system.
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no endocrine disruptor and PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex X



Section 3 Composition/ Information on ingredients

Substance/Mixture: Mixture

Ingredient(s):

Name	Product identifier	Concentration %	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lead	(CAS No) 7439-92-1 (EC no) 231-100-4	56-63%	Repr. 1A, H360 STOT RE 1, H372 Aquatic Acute 1 H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Antimony	(CAS No) 7440-36-0 (EC no) 231-146-5	0.05-0.03%	Repr. 1A, H360 Lact., H362 Aquatic Chronic 3, H412
Lead dioxide	CAS-No.: 1309-60-0 EC No.: 215-174-5	27-37%	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Inhalation:vapour), H332 Repr. 1A, H360 STOT RE 2, H373 Aquatic Acute 1, H400
Tin	CAS-No.: 7440-31-5 EC No.: 231-141-8	0.10-0.25%	Not classified

Name	Product identifier	Specific concentration limits
Lead	(CAS No) :7439-92-1 (EC no) : 231-100-4 (REACH no) : 01-2119458838- 20	(0.03 ≤C ≤ 100) Repr. 1A, H360D
Sulfuric Acid	CAS-No.: 7664-93-9 EC No.: 231-639-5	(5 ≤C < 15) Eye Irrit. 2, H319 (5 ≤C < 15) Skin Irrit. 2, H315 (15 ≤C ≤ 100) Skin Corr. 1A, H314

Section 4 First aid measures

4.1 Description of first aid measures:

In all cases of doubt, or when symptoms persist, seek medical attention.

4.1.1 In case of inhalation:

Sulfuric Acid: Remove to fresh air immediately. If breathing is difficult, give oxygen. Lead Compounds: Remove from exposure, gargle, wash nose and lips, consult physician.

4.1.2 In case of skin contact:



Sulfuric Acid: Flush with large amounts of water for at least 15 minutes, remove any contaminated clothing. If irritation develops seek medical attention. Lead Compounds: Wash with soap and water.

4.1.3 In case of eyes contact:

Sulfuric Acid: Flush immediately with water for 15 minutes, consult a physician. Lead Compounds: Flush immediately with water for 15 minutes, consult a physician.

4.1.4 In case of ingestion:

Sulfuric Acid: Do not induce vomiting, consult a physician immediately. Lead Compounds: Consult a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed:

Causes severe skin burns and eye damage. May damage fertility. May damage the unborn child. May cause harm to breast-fed children.

Acute Health Hazards:

Sulfuric Acid: Severe skin irritation, burns, damage to cornea may cause blindness, upper respiratory irritation. Lead Compounds: May cause abdominal pain, nausea, headaches, vomiting, loss of appetite, severe cramping, muscular aches and weakness, and difficulty sleeping. The toxic effects of lead are cumulative and slow to appear. It affects the kidneys, reproductive and central nervous systems. The symptoms of lead overexposure are listed above. Exposure to lead from a battery most often occurs during lead reclamation operations through the breathing or ingestion of lead dust or fumes.

Chronic Health Hazards:

Sulfuric acid: Possible scarring of the cornea, inflammation of the nose, throat and bronchial tubes, possible erosion of tooth enamel. Lead Compounds: May cause anemia, damage to kidneys and nervous system, and damage to reproductive system in both males and females.

Medical Conditions Generally Aggravated by Exposure: Inorganic lead and its compounds can aggravate chronic forms of kidney, liver, and neurological diseases. Contact of battery electrolyte (acid) with the skin may aggravate skin diseases such as eczema and contact dermatitis. Overexposure to sulfuric acid mist may cause lung damage and aggravate pulmonary conditions.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

Section 5 Fire-Fighting measures

5.1 Extinguishing media:

Suitable extinguishing media: Use dry chemical, foam or carbon dioxide.

Unsuitable extinguishing media: Not available.

5.2 Special hazards arising from the substance or mixture

Sealed batteries can emit hydrogen only if over charged (float voltage > 2.41 VPC). The gas enters the air through the vent caps. To ABS: Temperatures over 300 °C (572 °F) may release combustible gases. To PP: Temperatures over 380 °C (716 °F) may release combustible gases.

5.3 Advice for firefighters:

Wear positive pressure self-contained breathing apparatus. Wear fully protective suit.



Section 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

6.1.1 For non-emergency personnel: Use proper personal protective equipment as indicated in Section 8. Ensure adequate ventilation. Avoid contact with eyes. Wear protective equipment. Keep unprotected persons away.

6.1.2 For emergency responders: Wear positive pressure self-contained breathing apparatus if dust is generated.

6.2 Environmental Precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3 Methods for Containment and Cleaning up:

In case the release occurs, stop flow of material: contain/absorb small spills with dry sand, earth, and vermiculite. If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc. Wear acid-resistant clothing, boots, gloves, and face shield. Do not allow discharge of unneutralized acid to sewer. Spent Batteries - send to secondary lead smelter for recycling. Follow applicable federal, state and local regulations Neutralize as in preceding step. Collect neutralized material in sealed container and handle as hazardous waste as applicable.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Section 7 Handling and storage

7.1 Precautions for safe handling:

7.1.1 Protective measures: Ensure good ventilation/exhaustion at the workplace. Avoid contact with eyes. Keep ignition sources away - Do not smoke. Due to the battery's low internal resistance and high power density, high levels of short circuit current can be developed across the battery terminals. Do not rest tools or cables on the battery. Use insulated tools only. Follow all installation instructions and diagrams when installing or maintaining battery systems.

7.1.2 Advice on general occupational hygiene:

Do not eat, drink and smoke in work areas. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities:

Store batteries in a cool, dry, well ventilated area that are separated from incompatible materials and any activities which may generate flames, sparks, or heat. Keep away from all metallic articles that could contact the negative and positive terminals on a battery and create a short circuit condition. Battery should be stored under roof for protection against adverse weather conditions. Store and handle only in areas with adequate water supply and spill control. Avoid damage to battery case.



7.3 Specific end use(s):

Not applicable.

Section 8 Exposure Controls/ Personal Protection

8.1 Control parameters:

Lead (7439-92-1)		
EU	European BEI	(Medium: blood - Time: no restriction - Parameter: Lead (binding biological limit value) 0.075 mg/m3 (Medium: air - Time: 40 hours per week Parameter: Lead (TWA medical surveillance threshold in air measured as a time weighted average over 40 hours per week) (Medium: blood - Time: no restriction – Parameter : Lead (medical surveillance threshold measured in individual workers)
Austria	MAK (mg/m3)	0.1 mg/m3 (inhalable fraction)
Austria	MAK Short time value (mg/m3)	0.4 mg/m3 (inhalable fraction)
Bulgaria	OEL TWA (mg/m3)	0.05 mg/m3
Bulgaria	Bulgaria - BEI	300 µg/l (Medium: blood - Time: not fixed - Parameter: Lead (for women under 45 years old) 400 µg/l (Medium: blood - Time: not fixed - Parameter: Lead)
Lead (7439-92-1)		
Croatia	GVI (granična vrijednost izloženosti) (mg/m3)	0.15 mg/m3
Croatia	Croatia - BEI	(Medium: blood - Time: not critical - Parameter: Lead (Medical surveillance should be carried out when the limit value of Lead in blood of workers >40 µg/100mL blood) (Medium: urine - Time: single sample or urine collected over 24 hours - Parameter: Lead (For all results that are expressed on Creatinine, Creatinine concentration <0.5 g/L and >3.0 g/L should not be considered) (Medium: blood - Time: not critical - Parameter: delta.Aminolevulinic acid dehydratase) (Medium: blood - Time: after exposure during 2-3 months (light protected sample) - Parameter: Protoporphyrin in erythrocytes (Interference of Irondefi ciency (anemia sideropenic))
Cyprus	OEL TWA (mg/m3)	0.15 mg/m3
Czech Republic	Expoziční limity (PEL) (mg/m3)	0.05 mg/m3



Czech Republic	Czech Republic - BEI	<p>(Medium: urine - Time: discretionary - Parameter: 5 Aminolevulinic acid (For short term continual exposures <=30 calendar days)</p> <p>(Medium: urine - Time: discretionary - Parameter: Coproporphyrin (For short term continual exposures <=30 calendar days)</p> <p>(Medium: urine - Time: discretionary - Parameter: 5 Aminolevulinic acid (For short term continual exposures <=30 calendar days)</p> <p>(Medium: urine - Time: discretionary - Parameter: Coproporphyrin (For short term continual exposures <=30 calendar days)</p> <p>0.4 mg/l (Medium: blood - Time: discretionary -Parameter: Lead)</p>
Denmark	Grænseværdie (langvarig) (mg/m3)	0.05 mg/m3 (dust, fume and powder)
Denmark	Denmark - BEI	(Medium: blood - Parameter: Lead)
Estonia	OEL TWA (mg/m3)	0.1 mg/m3 (total dust) 0.05 mg/m3 (respirable dust)
Finland	HTP-arvo (8h) (mg/m3)	0.1 mg/m3 (all works)
Finland	Finland - BEI	(Medium: blood - Time: not critical - Parameter: Lead)
France	VME (mg/m3)	0.1 mg/m3 (restrictive limit)
France	France - BEI	<p>400 µg/l (Medium: blood - Parameter: Lead (biological limit value, men)</p> <p>300 µg/l (Medium: blood - Parameter: Lead (biological limit value, women)</p> <p>200 µg/l (Medium: blood - Parameter: Lead (medical surveillance value, men)</p> <p>100 µg/l (Medium: blood - Parameter: Lead (medical surveillance value, women)</p>
Germany	TRGS 903 (BGW)	<p>300 µg/l (Medium: whole blood - Time: no restriction Parameter: Lead (women age below 45 years)</p> <p>400 µg/l (Medium: whole blood - Time: no restriction Parameter: Lead (women 45 years and older)</p>
Gibraltar	OEL TWA (mg/m3)	0.15 mg/m3
Gibraltar	Gibraltar - BEI	<p>(Medium: blood - Time: no restriction - Parameter:Lead (binding biological limit value)</p> <p>0.075 mg/m3 (Medium: air - Time: 40 hours per week Parameter: Lead (medical surveillance threshold measured in individual employees)</p> <p>(Medium: blood - Time: no restriction - Parameter:Lead (medical surveillance threshold measured in individual employees)</p>
Greece	OEL TWA (mg/m3)	0.15 mg/m3
Hungary	AK-érték	0.15 mg/m3
Ireland	OEL (8 hours ref) (mg/m3)	0.15 mg/m3



Ireland	OEL (15 min ref) (mg/m3)	0.45 mg/m3 (calculated)
Italy	OEL TWA (mg/m3)	0.075 mg/m3
Italy	Italy - BEI	(Medium: blood - Time: end of workweek (Lead remediation must be performed when workers of fertile age have Lead in blood levels >40 µg/100mL)
Latvia	OEL TWA (mg/m3)	0.005 mg/m3
Latvia	Latvia - BEI	(Medium: blood - Parameter: Lead (reference value in blood for occupationally unexposed population <=10 µg/100 mL) (Medium: urine - Parameter: Coproporphyrin(reference value 22-57 µg/g Creatinine) (Medium: urine - Parameter: Aminolevulinic acid (reference value 0. 5-2.5mg/g Creatinine)
Lithuania	IPRV (mg/m3)	0.15 mg/m3 (inhalable fraction) 0.07 mg/m3 (respirable fraction)
Luxembourg	OEL TWA (mg/m3)	0.15 mg/m3
Luxembourg	Luxembourg - BEI	(Medium: blood - Parameter: Lead) 0.075 mg/m3 (Medium: blood - Parameter: Lead (medical surveillance threshold in air measured as a time weighted average over 40 hours per week) (Medium: blood - Parameter: Lead (medical surveillance threshold measured in individual workers)
Poland	NDS (mg/m3)	0.05 mg/m3
Portugal	OEL TWA (mg/m3)	0.15 mg/m3 (mandatory indicative limit value)
Romania	OEL TWA (mg/m3)	0.05 mg/m3
Romania	OEL STEL (mg/m3)	0.10 mg/m3
Romania	Romania - BEI	150 µg/l (Medium: urine - Time: end of shift - Parameter: Lead) (Medium: blood - Time: end of shift - Parameter: Lead) (Medium: hair - Time: end of shift - Parameter: Lead) 10 mg/l (Medium: urine - Time: end of shift - Parameter: .delta.-Aminolevulinic acid) 300 µg/l (Medium: urine - Time: end of shift - Parameter: Coproporphyrin) (Medium: blood - Time: end of shift - Parameter::Erythrocytes protoporphyrin)
Slovakia	NPHV (priemerna) (mg/m3)	0.15 mg/m3



Slovakia	Slovakia - BEI	<p>400 µg/l (Medium: blood - Time: not critical - Parameter: Lead)</p> <p>100 µg/l (Medium: blood - Time: not critical - Parameter: Lead (women younger than 45 years of age))</p> <p>15 mg/l (Medium: urine - Time: not critical - Parameter: .delta.-Aminolevulinic acid)</p> <p>6 mg/l (Medium: urine - Time: not critical - Parameter: .delta.-Aminolevulinic acid (women younger than 45 years of age))</p> <p>0.30 mg/l (Medium: urine - Time: not critical Parameter: Coproporphyrins)</p>
Slovenia	OEL TWA (mg/m3)	0.1 mg/m3 (inhalable fraction)
Slovenia	OEL STEL (mg/m3)	0.4 mg/m3 (inhalable fraction)
Spain	VLA-ED (mg/m3)	0.15 mg/m3
Spain		(Medium: blood - Time: not critical - Parameter: Lead (3,K))
Sweden	nivagränsvärde (NVG) (mg/m3)	<p>0.1 mg/m3 (total inhalable dust)</p> <p>0.05 mg/m3 (total respirable dust)</p>
United Kingdom	WEL TWA (mg/m3)	0.15 mg/m3
United Kingdom	WEL STEL (mg/m3)	0.45 mg/m3 (calculated)
Norway	Grenseverdier (AN) (mg/m3)	0.05 mg/m3 (dust and fume)
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	0.05 mg/m3 (dust and fume)
Switzerland	VME (mg/m3)	0.1 mg/m3 (inhalable dust)
Switzerland	VLE (mg/m3)	0.8 mg/m3 (inhalable dust)
Switzerland	Switzerland - BEI	<p>400 µg/l (Medium: whole blood - Time: no restrictions Parameter: Lead (men and women over 45 years old))</p> <p>100 µg/l (Medium: whole blood - Time: no restrictions Parameter: Lead (women less than 45 years old,))</p>
Australia	TWA (mg/m3)	0.15 mg/m3 (dust and fume)
Canada (Quebec)	VEMP (mg/m3)	0.05 mg/m3
USA - ACGIH	ACGIH TWA(mg/m3)	0.05 mg/m3
USA - IDLH	US IDLH (mg/m3)	100 mg/m3
USA - NIOSH	NIOSH REL (TWA) (mg/m3)	0.050 mg/m3
USA - OSHA	OSHA PEL (TWA) (mg/m3)	50 µg/m3



Sulfuric acid (7664-93-9)		
Bulgaria	OEL TWA (mg/m ³)	0.05 mg/m ³ (when choosing a suitable method for monitoring exposure should take into account potential constraints and interactions that may occur in the presence of other sulfur compounds-respirableaerosol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	0.05 mg/m ³
Cyprus	OEL TWA (mg/m ³)	0.05 mg/m ³ (vapor)
Czech Republic	Expoziční limity (PEL) (mg/m ³)	1mg/m ³ 0.05 mg/m ³ (concentrated-mist)
Denmark	Grænseværdie (langvarig) (mg/m ³)	0.05 mg/m ³ (thoracic fraction-mist)
Estonia	OEL TWA (mg/m ³)	1 mg/m ³ (fume)
Finland	HTP-arvo (8h) (mg/m ³)	0.05 mg/m ³
Finland	HTP-arvo (15 min)	0.1 mg/m ³
France	VME (mg/m ³)	0.05 mg/m ³ (thoracic fraction)
France	VLE (mg/m ³)	3 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	0.1 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-inhalable fraction)
Gibraltar	OEL TWA (mg/m ³)	0.05 mg/m ³ (when selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds-thoracic fraction)
Greece	OEL TWA (mg/m ³)	0.05 mg/m ³ (mist)
Hungary	AK-érték	0.05 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	0.05 ppm
Ireland	OEL (15 min ref) (ppm)	0.15 ppm (calculated)
Italy	OEL TWA (mg/m ³)	0.05 mg/m ³ (When choosing a suitable method for monitoring exposure should take into account potential constraints and interactions that may occur in the presence of other sulfur compounds, respirable fraction-thoracic fraction, mist)
Latvia	OEL TWA (mg/m ³)	0.05 mg/m ³ (possible limitations and the impact that may result from the presence of other Sulfurcomponents should be taken into account when choosing an appropriate exposure monitoring method-fog, which is defined as the thoracic fraction)
Lithuania	IPRV (mg/m ³)	0.05 mg/m ³ (vapor)
Lithuanra	TPRV (mg/m ³)	3 mg/m ³ (fog-vapor)
Luxembourg	OEL TWA (mg/m ³)	0.05 mg/m ³
Malta	OEL TWA (mg/m ³)	0.05 mg/m ³ (mist)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	0.05 mg/m ³ (defined as thoracic fraction-mist)



Poland	NDS (mg/m ³)	0.05 mg/m ³ (thoracic fraction)
Portugal	OEL TWA (mg/m ³)	0.05 mg/m ³ (thoracic fraction-mist)
Romania	OEL TWA (mg/m ³)	0.05 mg/m ³
Slovakia	NPHV (priemerná) (mg/m ³)	0.1 mg/m ³
Slovenia	OEL TWA (mg/m ³)	0.05 mg/m ³ (inhalable fraction, fog)
Spain	VLA-ED (mg/m ³)	0.05 mg/m ³ (indicative limit value-mist)
Sweden	nivågränsvärde (NVG) (mg/m ³)	0.1 mg/m ³
Sweden	kortidsvärde (KTV) (mg/m ³)	0.2 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	0.05 mg/m ³ (mist)
Norway	Grenseverdier (AN) (mg/m ³)	0.1 mg/m ³ (inhalable fraction)
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	0.1 mg/m ³ (inhalable fraction)
Switzerland	VME (mg/m ³)	0.1 mg/m ³ (inhalable dust)
Switzerland	VLE (mg/m ³)	0.1 mg/m ³ (inhalable dust)
Australia	TWA (mg/m ³)	1 mg/m ³
Australia	STEL (mg/m ³)	3 mg/m ³
Canada (Quebec;	VECD (mg/m ³)	3 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	1 mg/m ³
USA. ACGIH	ACGIH TWA (mg/m ³)	0.2 mg/m ³ (thoracic fraction)
USA – IDLH	US IDLH (mg/m ³)	15 mg/m ³
USA – NIOSH	NIOSH REL (TWA) (mg/m ³)	1 mg/m ³
USA. OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³

8.2 Exposure controls:

There are no special exposure controls for the handling, storage, installation or use of VRLA batteries.

8.2.1 Appropriate engineering controls: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

8.2.2 Individual protection measures, such as personal protective equipment:

Eye/face protection: None needed under normal conditions. If battery case is damaged, use chemical goggles or face shield.

Hand protection: None needed under normal conditions. If battery case is damaged, use rubber or plastic acid-resistant gloves with elbow-length gauntlet.

Body protection: None needed under normal conditions. If battery case is damaged wear acid-resistant apron. Under severe exposure or emergency conditions, wear acid



Respiratory protection:

–resistant clothing and boots.

None required under normal conditions. When concentrations of sulfuric acid mist are known to exceed PEL, use NIOSH or MSHA-approved respiratory protection.

Thermal hazards:

Wear suitable protective clothing to prevent heat.



8.2.3 Environmental exposure controls:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical state:	Solid
Colour:	Black
Odour:	Not available
Odour threshold:	Not available
pH:	Not available
Melting point/range (°C):	327.5°C(CAS# 7439-92-1)
Boiling point/range (°C):	1700°C(CAS# 7439-92-1)
Flash point (°C):	Not available
Evaporation rate:	Not available
Flammability limit - lower (%):	Not available
Flammability (solid, gas):	Non flammable(CAS# 7439-92-1)
Ignition temperature (°C):	Not available
Upper/lower flammability/explosive limits:	Not available
Vapour pressure (50°C):	1.33hPa
Vapour density:	Not available
Relative Density:	Not available
Bulk density (kg/m³):	11.34g/m ³
Water solubility (g/l):	Soluble in water
n-Octanol/Water (log Po/w):	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity, dynamic (mPa.s):	Not available
Explosive properties:	Not available
Oxidising properties:	Not available



Molecular Formula: Not applicable
Molecular Weight: 207.2

9.2. Other information:

Fat solubility(solvent– oil to be specified) etc: Not available
Surface tension: Not available
Dissociation constant in water(pKa): Not available
Oxidation-reduction Potential: Not available
Specific gravity: Not available

Section 10 Stability and reactivity

10.1 Reactivity: The substance is stable under normal storage and handling conditions.
10.2 Chemical stability: Stable at room temperature in closed containers under normal storage and handling conditions.
10.3 Possibility of hazardous reactions: No dangerous reactions known.
10.4 Conditions to avoid: Incompatible materials. High temperature, Sparks and other sources of ignition. Avoid mixing acid with other chemicals.
10.5 Incompatible materials: Potassium, carbides, sulphides, peroxides, phosphorus, sulphurs, ketone, ester, petrolatum. Reactive metals, strong bases, most organic compounds.
10.6 Hazardous decomposition products: Lead compounds and sulfuric acid fumes may be released during a fire involving the product

Section 11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Acute toxicity:
ATE_{mix}(oral): Not available
ATE_{mix}(inhalation): Not available
ATE_{mix}(Dermal): Not available
Sulphuric acid (CAS#7664-93-9)
LD50(Oral, Rat): 2140 mg/kg
LC50(Inhalation, Rat): Not available
LD50(Dermal, Rabbit): Not available
Skin corrosion/Irritation: Causes severe skin burns and eye damage.
Serious eye damage/irritation: Causes serious eye damage.
Respiratory or skin sensitization: Not classified
Germ cell mutagenicity: Not classified
Carcinogenicity: Not classified
Reproductive toxicity: Not classified
STOT- single exposure: Not classified
STOT-repeated exposure: Not classified
Aspiration hazard: Not classified



11.2 Information on other hazards

Endocrine disrupting properties

The mixture does not contain endocrine disruptor.

Other information

Not applicable

Section 12 Ecological information

12.1 Toxicity:

Lead (CAS: 7439-92-1):

Acute toxicity		Time	Species	Evaluation	Remarks
LC50	440 µg/L	96h	Fish	N/A	Species: Cyprinus carpio [semi-static]
LC50	1170 µg/L	96h	Fish	N/A	Species: Oncorhynchus mykiss [flow{hroughl}]
EC50	600 µg/L	48h	Daphnia	N/A	Species: water flea

Sulfuric Acid (CAS: 7664-93-9):

Acute toxicity		Time	Species	Evaluation	Remarks
LC50	82 mg/L	24h	Fish	N/A	Exposure time:24 h - Species: Brachydanio rerio [static]

12.2 Persistence and degradability:

Not available.

12.3 Bioaccumulative potential:

BCF fish 1; no bioaccumulation

12.4 Mobility in soil:

Not available.

12.5 Results of PBT & vPvB assessment:

Not applicable

12.6 Other adverse effects:

Not available.

Section 13 Disposal considerations

13.1 Waste treatment methods:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container to comply with applicable local, national and international regulations.

Recycling the product is recommended. Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

Consult the appropriate local waste disposal expert about waste disposal. Since emptied containers retain product residue, follow label warnings even after container is emptied.

European waste code :16 06 01- - lead batteries

Section 14 Transport information

	Land transport (ADR/RID)	Inland waterways (ADN)	Sea transport (IMDG)	Air transport (ICAO/IATA)
14.1 UN number or ID number	UN2794	UN2794	UN2794	UN2794
14.2 UN Proper shipping name	BATTERIES, WET, FILLED WITH ACID	BATTERIES, WET, FILLED WITH ACID	BATTERIES, WET, FILLED WITH ACID	BATTERIES, WET, FILLED WITH ACID
14.3 Transport hazard Class(es)	8	8	8	8
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No	No	No	No
14.6 Special precautions for user	See below	See below	See below	See below
14.7 Maritime transport in bulk according to IMO instruments	-	-	-	-

14.6 Special precautions for user

Land transport (ADR)

Classification code (ADR) : C11
 Special provisions (ADR) : 295,598
 Limited quantities (ADR) : 1L
 Excepted quantities (ADR) : E0
 Packing instructions (ADR) : P800,P801a
 Special packing provisions (ADR) : PP16
 Transport category (ADR) : 3
 Hazard identification number (Kemler No.) : 80
 Orange plates :



Tunnel restriction code (ADR) E
 EAC code 2R

Sea transport (IMDG)

Special provisions (IMDG) : 295
 Limited quantities (IMDG) : 1 L
 Excepted quantities (IMDG) : E0
 Packing instructions (IMDG) : P801
 EmS-No. (Fire) : F-A
 EmS-No. (Spillage) : S-B
 Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E0
 PCA Limited quantities (IATA) : Forbidden
 PCA limited quantity max net quantity (IATA) : Forbidden
 PCA packing instructions (IATA) : 870
 PCA max net quantity (IATA) : 30Kg



CAO packing instructions (IATA)	: 870
CAO max net quantity (IATA)	: No limit
Special provisions (IATA)	: A51, A164, A183
ERG code (IATA)	: 8L

Section 15 Regulation information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

REACH Annex XVII (Restriction List) : Not applicable.
REACH Annex XIV (Authorisation List) : Not applicable.
REACH Candidate List (SVHC) : Contains one substance (s) from the list of candidate substances of REACH: Lead (EC 231-100-4, CAS 7439-92-1)

Other EU regulations: Employment restrictions concerning young person must be observed. For use only by technically qualified individuals.

Other National regulations:

Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Sulfuric acid is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : Lead is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Lead is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Lead is listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product.

15.2 Chemical Safety Assessment

A chemical safety assessment has been carried out for the substance or the mixture by the supplier



Section 16 Other information

16.1 Indication of changes:

Version 4.0 Amended by (EU) 2020/878

16.2 Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
RID: Regulation for rail International transportation of Dangerous goods
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IMDG: Code international maritime dangerous goods code
ICAO: International Civil Aviation Organization
IATA: International Air Transport Association
UFI: Unique Formula Identifier
LC50: median lethal concentration
EC50: The effective concentration of substance that causes 50% of the maximum response.
NOEC: No Observed Effect Concentration
DNEL: derived no-effect level
PNEC: predicted no-effect concentration

16.3 Key literature references and sources for data

ECHA Registered substances data

16.4 Training instructions:

Not applicable.

16.5 Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

16.6 Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation
H318	Causes serious eye damage.
H319	Causes serious eye irritation
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H360D May damage the unborn child.	
H360FD	May damage fertility. May damage the unborn child.
H362	May cause harm to breast-fed children.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated
exposure.	
H400	Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.



This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.