

SLA MAX
FACTORY ACTIVATED

SLA MAX | PREMIUM QUALITY READY TO START

REF

BGZ20H**12v****VOLTAGE - V****320A****CCA - A (EN)****21.1Ah****CAPACITY - Ah (20Hr)****20Ah****CAPACITY - Ah (10Hr)****TECHNOLOGY**

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES


- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe

UPGRADE FOR


MF BTX20-BS
SLA BTX20

WEIGHT

Battery (with acid): approx 6.63kg

MOUNTING ANGLE**DIMENSIONS**

Length (A):	176mm ±2mm
Width (B):	89mm ±2mm
Container height:	154mm ±2mm
Total height (C):	154mm ±2mm

**TERMINALS (mm)**