



SLA MAX[®]

FACTORY ACTIVATED

SLA MAX | PREMIUM QUALITY READY TO START

REF Bgz16HL



12V VOLTAGE - V

240A CCA

16.8Ah CAPACITY - Ah (20Hr)

16Ah CAPACITY - Ah (10Hr)

TECHNOLOGY

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES

- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe


UPGRADE FOR

MF BTX14L-BS
SLA BTX14L
SLA MAX BTX14HL

WEIGHT


Battery (with acid): approx 5.48kg

MOUNTING ANGLE



DIMENSIONS

Length (A): 150mm ±2mm
Width (B): 88.5mm ±2mm
Container height: 145mm ±2mm
Total height (C): 145mm ±2mm



TERMINALS (mm)

