



SLA^{MAX}

FACTORY ACTIVATED

SLA MAX | PREMIUM QUALITY READY TO START

REF BTX14AH



- 12V** VOLTAGE - V
- 240A** CCA - A (EN)
- 13.7Ah** CAPACITY - Ah (20Hr)
- 13Ah** CAPACITY - Ah (10Hr)

TECHNOLOGY

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES

- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe


UPGRADE FOR

DRY BB14-A2 (12N14-4A) ; BB14-B2
 MF BTX14AH-BS
 SLA BB14-A2/B2 /BTX14AH

WEIGHT


Battery (with acid): approx 5.10kg

MOUNTING ANGLE



DIMENSIONS

Length (A):	134mm ±2mm
Width (B):	89mm ±2mm
Container height:	164mm ±2mm
Total height (C):	164mm ±2mm



TERMINALS (mm)

