


DRY | CONVENTIONAL



Conventional batteries are Lead Acid flooded batteries that must be filled before first use with a periodic maintenance. Conventional batteries include a sulfation retardant technology which reduces battery-killing plate sulfation. This results in a longer battery life, especially in standby or storage mode. These conventional batteries are perfectly suitable for entry-level powersport and lawn & garden vehicles with standard requirements.



Acid pack included for activation

COMPATIBLE CHARGERS

BS 10	Battery size up to 20Ah
BS 15	Battery size up to 30Ah
BS 30	Battery size up to 60Ah
BS 60	Battery size up to 120Ah
BK 20	Battery size up to 40Ah



Acid pack included
For initial filling



Periodic maintenance
Refilled with water if necessary



Handle with care to prevent acid spillage



Long shelf life
No need to be recharged while stocked



Internal gas emission through venting hole



Wide variety of 6V & 12V models

MOUNTING ANGLES

UPRIGHT INCLINATION ONLY



DID YOU KNOW?

Since February 1st, 2021, the regulation (EU) 2019/1148 prohibits the sale of acid batteries to the public in Europe.

DRY batteries can be stored for several years, as it is a dry-charged battery.

TECHNICAL FEATURES | DRY

12V

BS BATTERY TYPE HIGH PERFORMANCE	BS CODE	CAPACITY AH (10HR)	CAPACITY AH (20HR)	CCA A (-18°C)	DIMENSIONS (±2MM)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BB2.5L-C	310729	2.5	2.6	20	80	70	105		-
BB3L-A	310589	3	3.2	30	98	56	110		B
BB3L-B	310588	3	3.2	30	98	56	110		B
BB4L-B	310590	4	4.2	50	120	70	92		A
BB4L-A	310661	4	4.2	50	120	70	92		A
BB5L-B	310591	5	5.3	65	120	60	130		B
BB6.5L-B	310732	6.5	7	65	138	73	107		B
BB7B-B	310662	7	7.4	85	150	60	130		B
BB7-A	310592	8	8.4	105	135	75	133		B
BB7C-A	310593	8	8.4	85	130	90	114		E
BB7L-B	310594	8	8.4	85	135	75	133		B
BB7L-B2	310595	8	8.4	85	135	75	133		A
BB9-B	310596	9	9.5	115	135	75	139		B
BB9L-B	310599	9	9.5	115	135	75	139		B
BB9L-A2	310598	9	9.5	100	135	75	139		A
BB9A-A	310597	9	9.5	100	135	75	155		B
BB10L-A2	310556	11	11.6	130	135	90	145		D
BB10L-B	310555	11	11.6	130	135	89	145		B
BB10L-B2	310557	11	11.6	130	135	89	145		D
BB10L-BP	310558	11	11.6	165	135	89	145		B
BB10A-A2	310660	11	11.6	160	135	89	155		D
BB12A-A	310561	12	12.6	155	134	81	160		B
BB12A-B	310562	12	12.6	155	134	81	160		B
BB12AL-A/A2	310564	12	12.6	155	134	80	160		B
BB12C-A	310566	12	12.6	155	134	80	175		A
BB14-A2	310567	14	14.7	175	134	89	166		D
BB14-B2	310568	14	14.7	175	134	89	166		D
BB14L-A	310778	14	14.7	190	134	89	166		B
BB14L-A2	310569	14	14.7	175	134	89	166		D
BB14L-B2	310570	14	14.7	175	134	89	166		D
SBB14L-A2	310575	14	14.7	175	134	89	166		D
SBB14L-B2	310741	14	14.7	175	134	89	166		D
BB14A-A2	310571	14	14.7	175	134	89	176		D
BB16-B	310577	19	20	215	175	100	155		B
BB16L-B	310578	19	20	215	175	100	155		B
BB16HL-A-CX	310822	19	20	255	175	100	155		B
BB16B-A	310580	16	16.8	210	160	90	161		A
BB16B-A1	310581	16	16.8	210	160	90	161		C
BB16AL-A2	310576	16	16.8	210	207	71.5	164		F
HBB16A-A/AB	310582	16	16.8	210	151	91	180		C

TERMINAL TYPE



DRY | TECHNICAL FEATURES

12V	BS BATTERY TYPE HIGH PERFORMANCE	BS CODE	CAPACITY AH (10HR)	CAPACITY AH (20HR)	CCA A (-18°C)	DIMENSIONS (±2MM)			ASSEMBLY LAYOUT	TERMINAL
						L	W	H		
	BB16CL-B	310579	19	20	250	175	100	175		A
	B50-N18L-A/A2/12N18-3A	310547	20	21.1	250	205	90	162		C
	B50-N18L-A3	310548	20	21.1	250	205	90	162		A
	SB50-N18L-AT	310656	20	21.1	250	205	90	162		C
	B50-N18A-A	310657	20	21.1	250	205	90	176		C
	BB18-A	310585	18	18.9	235	180	90	162		C
	BB18L-A	310586	18	18.9	235	180	90	162		C
	BB18L-A2	310727	18	18.9	235	180	90	162		C
	B60-N24-A	310551	28	29.5	280	184	124	175		G
	B60-N24L-A	310658	28	29.5	280	184	124	175		G
	B60-N24AL-B	310550	28	29.5	280	184	124	175		G
	B60-N30L-A	310554	30	31.6	300	184	130	170		G
	BB30L-B	310552	30	31.6	300	165	130	176		A
	BB30CL-B	310553	30	31.6	300	165	130	192		A
	BHD-12	310601	29	29.5	280	205	130	165		H
	51814	310545	-	19	210	186	82	171		-
	51913	310542	-	19	210	186	82	171		-
	52515	310543	-	30	300	184	130	170		G
	53030	310544	-	30	300	184	130	170		G
	53034	310659	-	31	300	184	130	170		G

12V	BS BATTERY TYPE	BS CODE	CAPACITY AH (10HR)	CAPACITY AH (20HR)	CCA A (-18°C)	DIMENSIONS (±2MM)			ASSEMBLY LAYOUT	TERMINAL
						L	W	H		
	12N5-3B	310533	5	5.3	40	120	61	130		B
	12N5.5-3B	310529	5.5	5.8	55	135	60	130		B
	12N5.5-4A	310530	5.5	5.8	55	135	60	130		F
	12N5.5-4B	310531	5.5	5.8	55	135	60	130		B
	12N5.5A-3B	310532	5.5	5.8	55	103	90	114		-
	12N6.5-3B	310901	6.5	6.8	55	137	66	100		B
	12N7-3A	310795	7	7.4	75	135	75	133		B
	12N7-3B	310534	7	7.4	75	135	75	133		B
	12N7-4A	310645	7	7.4	75	135	75	133		B
	12N7-4B	310535	7	7.4	75	135	75	133		B
	12N7A-3A	310800	7	7.4	70	150	60	130		B
	12N7A-4A	310902	7	7.4	70	150	60	130		B
	12N9-3B	310538	9	9.5	85	135	75	139		B
	12N9-4B-1	310537	9	9.5	85	135	75	139		B
	12N12A-4A-1	310527	12	12.6	120	134	81	160		B
	12N14-3B	310772	14	14.7	135	134	89	166		D



TECHNICAL FEATURES | DRY

6V

BS BATTERY TYPE	BS CODE	CAPACITY AH (10HR)	CAPACITY AH (20HR)	CCA A (-18°C)	DIMENSIONS (±2MM)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
6N2A-2C	310508	2	2.1	-	70	47	96		-
6N4-2A	310509	4	4.2	-	71	71	96		-
6N4-2A-2	310708	4	4.2	-	71	71	96		-
6N4-2A-3	310709	4	4.2	-	71	71	96		-
6N4-2A-4	310510	4	4.2	-	71	71	96		-
6N4-2A-6	310710	4	4.2	-	71	71	96		-
6N4-2A-7	310512	4	4.2	-	71	71	96		-
6N4-2A-8	310711	4	4.2	-	71	71	96		-
6N4A-4D	310513	4	4.2	-	61	57	130		-
6N4B-2A	310514	4	4.2	-	102	48	96		-
6N4B-2A-3	310515	4	4.2	-	102	48	96		-
6N4B-2A-4	310714	4	4.2	-	102	48	96		-
6N4B-2A-5	310705	4	4.2	-	102	48	96		-
6N6-3B	310518	6	6.3	-	99	57	111		B
6N6-3B-1	310519	6	6.3	-	99	57	111		B
6N6-1D-2	310517	6	6.3	-	99	57	111		-
B49-6	310522	10	10.5	-	91	83	160		B
B38-6A	310520	13	13.7	-	119	83	161		B
6N11-2D	310503	11	11.6	-	150	70	100		B
6N11A-1B	310501	11	11.6	-	122	62	131		B
6N11A-4	310646	11	11.6	-	122	62	131		B
6N11A-3A	310500	11	11.6	-	122	62	131		B
6N11A-4A	310502	11	11.6	-	122	62	131		B
B54-6 (6N12A-2C)	310523	12	12.6	-	156	57	116		B
B54-6A (6N12A-2D)	310504	12	12.6	-	156	57	116		B
6BB8L-B	310806	8	8.4	-	120	70	95		B

Non-exhaustive list

DID YOU KNOW?

Our SLA (Sealed Lead Acid) range, factory activated and ready to use, can replace 95% of DRY batteries.

DRY batteries are not suitable for e-commerce SINCE 2021, a European decree prohibits handling of acid by the end user.

BATTERY RANGE OVERVIEW

COMPARATIVE CHART



	LITHIUM LiFePO4 MAX	LITHIUM LiFePO4	SLA FACTORY ACTIVATED	SLA FACTORY ACTIVATED MAX	MF BATTERY	DRY BATTERY
PLUG & PLAY	✓	✓	✓	✓	—	—
NO ACID HANDLING	✓	✓	✓	✓	—	—
NO MAINTENANCE	✓	✓	✓	✓	✓ ⁽¹⁾	—
NON-SPILLABLE	✓	✓	✓	✓	—	—
FACTORY ACTIVATED	✓	✓	✓	✓	—	—
MULTI-POSITIONING FITMENT	✓	✓	✓	✓	—	—
EASY TO CARRY	✓	✓	✓	✓	—	—
EASY TO SHIP	✓	✓	✓	✓	—	—
NO SELF DISCHARGE DURING STORAGE	—	—	—	—	✓	✓
SUITABLE FOR E-COMMERCE COMPLIANT WITH EU REGULATION 2019/1148 (FOR THE SALE OF ACID FOR BATTERIES)	✓	✓	✓	✓	—	—

TRANSPORTATION CHART

TRANSPORT TYPE			
	SUITABLE FOR E-COMMERCE		UNDER CERTAIN CONDITION

(1) Once activated

(2) According to ADR, IMDG & IATA regulations