# LITHIUM MAX INNOVATION FOR MAXIMUM PERFORMANCE Designed to offer maximum performance thanks to highly reduced weight law self-discharge, much langur

Designed to offer maximum performance thanks to highly reduced weight, low self-discharge, much longer battery life. The Lithium Max battery range is specially developed to meet the superior needs of off-road motorcycles, V-Twins, ATVs, UTVs and SSVs.



# MAX



### **READY TO USE**

Just plug & play.



### LIGHTER WEIGHT

Up to 70% lighter than Lead Acid batteries.



### **EXTENSIVE CYCLE LIFE**

Over 2 000 cycles.



### **HEAT RESISTANCE**

Up to 230°C.



### **ROBUST BRASS TERMINALS**

To enhance electrical performance.



### STATE OF CHARGE INDICATOR

Monitor the state of charge with the indicator screen on the top.



### HIGHEST STARTING POWER

Up to 900A.



### **HIGHEST CAPACITY**

Up to 2 times that of the Lithium range.


Note: lithium motorcycle batteries can't be charged over 15V and require a specific charger for lithium technology.





### MOUNTING ANGLES

### **HIGH INCLINATION**



# COMPATIBLE CHARGERS

**B510**Battery size up to 20Ah

**B5 30**Battery size up to 60Ah

BK 20 Battery size up to 40Ah

### **DID YOU KNOW?**

Our BSLi-10 Max & BSLi-12 Max battery casings are designed to fit with original Lead Acid batteries no spacers are required.

Lithium batteries exceeding 100Wh must be shipped as dangerous goods. Our Lithium Max batteries are packaged with UN mastercarton according to international transportation standards.



## 12V - TECHNICAL FEATURES

| BS TYPE     | BS CODE | POWER<br>(Wh) | CCA<br>(A) | CAPACITY<br>AH (10Hr) | DIMENSIONS (±2mm) |     |     | DOL LEITY | TED. 1111 | REPLACEMENT - MOST POPULAR MODELS |   |
|-------------|---------|---------------|------------|-----------------------|-------------------|-----|-----|-----------|-----------|-----------------------------------|---|
|             |         |               |            |                       | L                 | W   | Н   | POLARITY  | TERMINAL  | LITHIUM                           | SLA/SLA MAX   |
| BSLi-02 MAX | 360115  | 36            | 180        | 3                     | 114               | 70  | 85  |           | M5        | BSLi-02                           | 12N5.5-3B BB4L-B BB5L-B BB7C-A BB7L-B2 BTX4L+/BTZ5S BTX5L/BTZ6S BTZ7S BTX7L BTZ7V BTZ8V |
| BSLi-10 MAX | 360116  | 180           | 750        | 15                    | 175               | 87  | 155 |           | M6        | BSLi-10                           | BGZ20HL BTX20HL BTX24HL/B50N18L-A/A2/A BTX20L-BS BTX20HL-BS BTX24HL-BS BB18L-A          |
| BSLi-12 MAX | 360117  | 216           | 900        | 18                    | 166               | 127 | 175 |           | ₩6        | BSLi-12                           | BGZ32HL<br>BIX30L<br>BIX30HL<br>BIX30L-BS<br>BB30L-B<br>53030                           |





**LARGER POUCH CELLS** 

For enchanced CCA, capacity and higher performance.



www.bs-battery.com 15