LITHIUM MAX INNOVATION FOR MAXIMUM PERFORMANCE

Designed to offer maximum performance thanks to highly reduced weight, low self-discharge, much longer battery life. The Lithium Max battery range is specially developed to meet the superior needs of off-road motorcycles, V-Twins, ATVs, UTVs and SSVs.



MAX



READY TO USE

Just plug & play.



LIGHTER WEIGHT

Up to 70% lighter than Lead Acid batteries.



EXTENSIVE CYCLE LIFE

Over 2 000 cycles.



HEAT RESISTANCE

Up to 230°C.



ROBUST BRASS TERMINALS

To enhance electrical performance.



STATE OF CHARGE INDICATOR

Monitor the state of charge with the indicator screen on the top.



HIGHEST STARTING POWER

Up to 900A.



HIGHEST CAPACITY

Up to 2 times that of the Lithium range.

Note: lithium motorcycle batteries can't be charged over 15V and require a specific charger for lithium technology.








MOUNTING ANGLES

HIGH INCLINATION



COMPATIBLE CHARGERS

B510Battery size up to 20Ah

B5 30Battery size up to 60Ah

BK 20 Battery size up to 40Ah

DID YOU KNOW?

Our BSLi-10 Max & BSLi-12 Max battery casings are designed to fit with original Lead Acid batteries no spacers are required.

Lithium batteries exceeding 100Wh must be shipped as dangerous goods. Our Lithium Max batteries are packaged with UN mastercarton according to international transportation standards.



12V - TECHNICAL FEATURES

BS TYPE	BS CODE	POWER (Wh)	CCA (A)	CAPACITY AH (10Hr)	DIMENSIONS (±2mm)			POLARITY	TERMINAL	REPLACEMENT - MOST POPULAR MODELS	
BSTYPE					L	W	Н	PULAKITY	TERMINAL	LITHIUM	SLA/SLA MAX
BSLi-02 MAX	360115	36	180	3	114	70	85		M5	BSLi-02	12N5.5-3B BB4L-B BB5L-B BB7C-A BB7L-B2 BTX4L+/BTZ5S BTX5L/BTZ6S BTZ7S BTX7L BTZ7V BTZ8V
BSLi-10 MAX	360116	180	750	15	175	87	155		M6	BSLi-10	BGZ20HL BTX20HL BTX24HL/B50N18L-A/A2/A BTX20L-BS BTX20HL-BS BTX24HL-BS BB18L-A
BSLi-12 MAX	360117	216	900	18	166	127	175		M6	BSLi-12	BGZ32HL BIX30L BIX30HL BIX30L-BS BB30L-B 53030





For enchanced CCA, capacity and higher performance.



www.bs-battery.com 15