

CHARGER DATASHEET



SMARTBANKBATTERYCHARGER & MAINTAINER WITHRECONDITIONINGFUNCTION

100% AUTOMATIC | 6V/12V - 3x 2A **LEAD ACID & LITHIUM**



BOX CONTENT



SUITABLE FOR



FEATURES

- · Charges and maintains 3 batteries with different voltage and technologies at once
- Auto detect Lead Acid or Lithium technology
- Adaptable charging algorithm for Lead Acid & Lithium (LiFePO4)
- · Force mode: to activate low voltage "dead" Lead Acid battery or wake up "dead" LiFePO4 battery
- · Easy to use: connect & forget
- · Safe: connection spark free, reverse polarity, short circuit and internal overheat protection

TECHNICAL DATA


| Input voltage | 100-240VAC, 50-60Hz |
|-------------------------|---|
| Charging voltage | 7.2VDC (6V) / 14.4VDC (12V) |
| Charging current | 2A per channel |
| Type of charger | Automatic - 10 stages |
| Type of battery | 6V & 12V Lead Acid or 12V LiFePO4 |
| Battery size | Up to 40Ah (up to 80Ah for maintenance) |

BATTERY COMPATIBILITY



Lithium LiFeP04

CHARGING CURVE



- * Only if force mode is selected:
- For lead acid: reconditioning stage
- For lithium: wake-up stage
- ** No float & maintenance stages for Lithium. Once the battery is fully charged, the charge is stopped



