

SLA MAX
FACTORY ACTIVATED

SLA MAX | PREMIUM QUALITY READY TO START

REF **51913****12V** VOLTAGE - V**275A** CCA - A (EN)**22Ah** CAPACITY - Ah (20Hr)**21Ah** CAPACITY - Ah (10Hr)

TECHNOLOGY

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Activated and pre-charged batteries
- Homologated by OEM

FEATURES

- Factory activated: Ready-to-start battery
- Totally sealed
- Safe & Environmentally friendly
- Superior capacity
- Increased power & Extended life
- Low discharge rate
- Absolutely maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Extreme vibration resistance
- Spillproof design
- Multi-positional fitment
- No acid handling - Very safe


UPGRADE FOR

DRY 51814 ; 51913
SLA SLA12-19

WEIGHT


Battery (with acid): approx 6.04kg

MOUNTING ANGLE




DIMENSIONS


Length (A):	183mm ±2mm
Width (B):	79mm ±2mm
Container height:	171mm ±2mm
Total height (C):	171mm ±2mm



TERMINALS (mm)



FRONT



SIDE



TOP