

BGZ SERIES

THE LATEST SLA MAX GENERATION
MAXIMUM PERFORMANCE FOR BIG ENGINES



SLA MAX | BGZ SERIES



**plug
and
play**



	BGZ16H	BGZ16HL	BGZ20H	BGZ20HL	BGZ32HL
PN	300931	300932	300938	300939	300935
NOMINAL VOLTAGE	12V	12V	12V	12V	12V
NOMINAL CAPACITY 10Hr	16Ah	16Ah	20Ah	20Ah	32Ah
NOMINAL CAPACITY 20Hr	16.8Ah	16.8Ah	21.1Ah	21.1Ah	33.7Ah
CCA	240A	240A	360A	360A	500A
DIMENSIONS	5.90 x 3.46 x 5.70 in	5.90 x 3.46 x 5.70 in	6.93 x 3.50 x 6.18 in	6.93 x 3.50 x 6.18 in	6.69 x 5.19 x 6.88 in
WEIGHT	12.08 lbs	12.08 lbs	15.34 lbs	15.34 lbs	22.88 lbs
BATTERY REPLACEMENT	BTX14H BTX14 BTX14-BS	BTX14HL BTX14L BTX14L-BS	BTX20H BTX20-BS	BTX20HL BTX20L-BS BTX20HL-BS BB18L-A	BIX30HL BIX30L BIX30L-BS BB30L-B


TALLER PLATES

For enhanced CCA & Capacity



BUILT-IN COPPER NUTS

Enhanced conductivity (up to 50% than standard terminal) & improved max torque strength (up to 13N.m)



FRONT & TOP CONNECTIONS

Designed to facilitate the mounting on Heavy Duty motorcycles

FEATURES



FACTORY ACTIVATED
AGM (Absorbent Glass Mat) technology.



READY TO USE
Just plug & play.



NO MAINTENANCE
VRLA (Valve Regulated Lead Acid) design.



SPILL-PROOF DESIGN
Factory sealed & electrolyte held in a glass fiber mat.



NO ACID HANDLING
Very safe.



EXTREME VIBRATION RESISTANCE
Reinforced battery case.



MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE
20% higher than SLA CCA.



SUPERIOR CAPACITY
20% higher than SLA capacity.