




CHARGER SELECTION CHART



BS 10 BS 30 BS 30 MAX BK 20 BS 15 BS 60

BATTERY TECHNOLOGY	AUTO-DETECT LEAD ACID & LITHIUM			LEAD ACID	
BATTERY VOLTAGE (V)	6 & 12	12	6 & 12	12	
BATTERY CAPACITY (Ah)	UP TO 20	UP TO 60	UP TO 40	UP TO 30	UP TO 120
BATTERY CAPACITY FOR MAINTENANCE (Ah)	UP TO 40	UP TO 120	UP TO 80	UP TO 60	UP TO 180
CHARGING CURRENT (A)	1	3	3x 2	1.5	1 - 4 - 6
CHARGING PROGRAM	9 STAGES		10 STAGES		8 STAGES
RECONDITIONING FUNCTION	NO		YES		YES
POWER SUPPLY FUNCTION	NO		YES	NO	NO
CAN BUS MODE	NO		YES	NO	NO
USERS TYPE	 FOR END-USERS		 FOR PROFESSIONALS		 FOR END-USERS
GOOD TO KNOW	WALL MOUNT CONNECTION	MULTIAXIS HOOK	DISPLAY PARTS (OPTION page 58)		MULTIAXIS HOOK
SUITABLE FOR	