

DRY

CONVENTIONAL

DRY batteries are Lead Acid **flooded** batteries that must be filled before the first use with **periodic maintenance**. These **conventional** batteries are perfectly suitable for entry-level powersport vehicles with standard requirements.



TO BE ACTIVATED
DRY-charged technology.



ACID PACK INCLUDED
For initial filling.



PERIODIC MAINTENANCE
Refilled with water if necessary.



HANDLE WITH CARE TO PREVENT ACID SPILLAGE



LONG SHELF LIFE
No need to be recharged while stocked (if not activated).





INTERNAL GAS EMISSION THROUGH VENTING HOLE



WIDE VARIETY OF 6V & 12V MODELS

MOUNTING ANGLES

UPRIGHT INCLINATION ONLY



COMPATIBLE CHARGERS

BS 10 Battery size up to 20Ah **BS 30** Battery size up to 60Ah

BS 30 MAX Battery size up to 60Ah **BK 20** Battery size up to 40Ah

DID YOU KNOW?

As they are not activated (dry-charged), DRY batteries can be stored for several years.

BS BATTERY TYPE HIGH PERFORMANCE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (IN)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BB2.5L-C	310729	2.5	2.6	20	3,15	2,76	4,13		-
BB3L-A	310589	3	3.2	30	3,86	2,21	4,33		B
BB3L-B	310588	3	3.2	30	3,86	2,21	4,33		B
BB4L-B	310590	4	4.2	50	4,72	2,76	3,62		A
BB5L-B	310591	5	5.3	65	4,72	2,36	5,12		B
BB6.5L-B	310732	6.5	7	65	5,43	2,87	4,21		B
BB7B-B	310662	7	7.4	85	5,91	2,36	5,12		B
BB7-A	310592	8	8.4	105	5,32	2,95	5,24		B
BB7C-A	310593	8	8.4	85	5,12	3,54	4,49		E
BB7L-B	310594	8	8.4	85	5,32	2,95	5,24		B
BB7L-B2	310595	8	8.4	85	5,32	2,95	5,24		A
BB9-B	310596	9	9.5	115	5,32	2,95	5,47		B
BB9L-B	310599	9	9.5	115	5,32	2,95	5,47		B
BB9L-A2	310598	9	9.5	100	5,32	2,95	5,47		A
BB9A-A	310597	9	9.5	100	5,32	2,95	6,1		B
BB10L-A2	310556	11	11.6	130	5,32	3,54	5,71		D
BB10L-B	310555	11	11.6	130	5,32	3,5	5,71		B
BB10L-B2	310557	11	11.6	130	5,32	3,54	5,71		D
BB10L-BP	310558	11	11.6	165	5,32	3,5	5,71		B
BB12A-A	310561	12	12.6	155	5,28	3,19	6,3		B
BB12A-B	310562	12	12.6	155	5,28	3,19	6,3		B
BB12AL-A/A2	310564	12	12.6	155	5,28	3,15	6,3		B
BB12C-A	310566	12	12.6	155	5,28	3,15	6,89		A
BB14-A2	310567	14	14.7	175	5,28	3,5	6,54		D
BB14-B2	310568	14	14.7	175	5,28	3,5	6,54		D
BB14L-A	310778	14	14.7	190	5,28	3,5	6,54		B
SBB14L-A2	310575	14	14.7	175	5,28	3,5	6,54		D
SBB14L-B2	310741	14	14.7	175	5,28	3,5	6,54		D
BB14A-A2	310571	14	14.7	175	5,28	3,5	6,93		D
BB16-B	310577	19	20	215	6,89	3,94	6,10		B
BB16L-B	310578	19	20	215	6,89	3,94	6,10		B
BB16HL-A-CX	310822	19	20	255	6,89	3,94	6,10		B
BB16B-A	310580	16	16.8	210	6,30	3,54	6,34		A
BB16B-A1	310581	16	16.8	210	6,30	3,54	6,34		C
BB16AL-A2	310576	16	16.8	210	8,15	2,82	6,46		F
HBB16A-A/AB	310582	16	16.8	210	5,95	3,58	7,09		C

TERMINAL
TYPE



12V - TECHNICAL FEATURES

DRY
BATTERY

BS BATTERY TYPE HIGH PERFORMANCE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (IN)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BB16CL-B	310579	19	20	250	6,89	3,94	6,89		A
B50-N18L-A/A2/12N18-3A	310547	20	21.1	250	8,07	3,54	6,38		C
B50-N18L-A3	310548	20	21.1	250	8,07	3,54	6,38		A
BB18L-A	310586	18	18.9	235	7,09	3,54	6,38		C
B60-N24L-A	310658	28	29.5	280	7,24	4,88	6,89		G
B60-N30L-A	310554	30	31.6	300	7,24	5,12	6,69		G
BB30L-B	310552	30	31.6	300	6,5	5,12	6,93		A
BB30CL-B	310553	30	31.6	300	6,5	5,12	7,56		A
BHD-12	310601	29	29.5	280	8,07	5,12	6,5		H
51814	310545	-	19	210	7,32	3,23	6,73		G
51913	310542	-	19	210	7,32	3,23	6,73		G
52515	310543	-	30	300	7,24	5,12	6,69		G
53030	310544	-	30	300	7,24	5,12	6,69		G
53034	310659	-	31	300	7,24	5,12	6,69		G

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (IN)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
12N5-3B	310533	5	5.3	40	4,72	2,4	5,12		B
12N5.5-3B	310529	5.5	5.8	55	5,32	2,36	5,12		B
12N5.5-4A	310530	5.5	5.8	55	5,32	2,36	5,12		F
12N7-3B	310534	7	7.4	75	5,32	2,95	5,24		B
12N7-4A	310645	7	7.4	75	5,32	2,95	5,24		B
12N7-4B	310535	7	7.4	75	5,32	2,95	5,24		B
12N7A-3A	310800	7	7.4	70	5,91	2,36	5,12		B
12N9-3B	310538	9	9.5	85	5,32	2,95	5,47		B
12N9-4B-1	310537	9	9.5	85	5,32	2,95	5,47		B
12N12A-4A-1	310527	12	12.6	120	5,28	3,19	6,3		B
12N14-3B	310772	14	14.7	135	5,28	3,5	6,54		D

TERMINAL TYPE	A	B	C	D	E	F	G	H	I	J

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (IN)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
6N4-2A-2	310708	4	4.2	-	2,8	2,8	3,78		-
6N4-2A-4	310510	4	4.2	-	2,8	2,8	3,78		-
6N4-2A-7	310512	4	4.2	-	2,8	2,8	3,78		-
6N4A-4D	310513	4	4.2	-	2,4	2,24	5,12		-
6N4B-2A	310514	4	4.2	-	4,02	1,89	3,78		-
6N4B-2A-3	310515	4	4.2	-	4,02	1,89	3,78		-
6N6-3B	310518	6	6.3	-	3,9	2,24	4,37		B
6N6-3B-1	310519	6	6.3	-	3,9	2,24	4,37		B
B49-6	310522	10	10.5	-	3,58	3,27	6,3		B
B38-6A	310520	13	13.7	-	4,69	3,27	6,34		B
6N11A-3A	310500	11	11.6	-	4,8	2,44	5,16		B
B54-6A (6N12A-2D)	310504	12	12.6	-	6,14	2,24	4,57		B
6BB8L-B	310806	8	8.4	-	4,72	2,76	3,74		B

Non-exhaustive list.



DID YOU KNOW?

95% of DRY batteries can be replaced by our SLA battery range.