

## 12N7-4A

BS CODE: **310645**

VOLTAGE **12V**

CCA **105A**


CAPACITY 20HR **8.4Ah**

CAPACITY 10HR **8.0Ah**



### DIMENSIONS

<b>LENGTH</b>	135 ±2mm	5.31 ±0.08inch
<b>WIDTH</b>	75 ±2mm	2.95 ±0.08inch
<b>TOTAL HEIGHT</b>	133 ±2mm	5.24 ±0.08inch
<b>WEIGHT</b>	1.9 kg ±5%	4.19 lbs ±5%




### TERMINAL (mm)

<b>POLARITY</b>	
<b>FRONT</b>	<b>SIDE</b>
	<b>TOP</b>

### DRY FEATURES

- TO BE ACTIVATED**  
DRY-charged technology.
- ACID PACK INCLUDED**  
For initial filling.
- PERIODIC MAINTENANCE**  
Refilled with water if necessary.
- HANDLE WITH CARE TO PREVENT ACID SPILLAGE**
- LONG SHELF LIFE**  
No need to be recharged while stocked (if not activated).
- INTERNAL GAS EMISSION THROUGH VENTING HOLE**
- WIDE VARIETY OF 6V & 12V MODELS**

### MOUNTING ANGLE



### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-