

BB14A-A2

BS CODE: 310571

VOLTAGE **12V**

CCA **175A**

CAPACITY 20HR **14.7Ah**

CAPACITY 10HR **14.0Ah**



DIMENSIONS

LENGTH	134 ±2mm	5.28 ±0.08inch
WIDTH	89 ±2mm	3.5 ±0.08inch
TOTAL HEIGHT	176 ±2mm	6.93 ±0.08inch
WEIGHT	3.02 kg ±5%	6.66 lbs ±5%

Technical drawings showing front, side, and top views of the battery with dimensions: 176±2 (height), 134±2 (length), 89±2 (width), 106±0.5 (terminal width), 144±2 (terminal length), and 30±0.5 (terminal height).

TERMINAL (mm)

POLARITY		
FRONT		SIDE
		TOP

DRY FEATURES

- TO BE ACTIVATED**
DRY-charged technology.
- ACID PACK INCLUDED**
For initial filling.
- PERIODIC MAINTENANCE**
Refilled with water if necessary.
- HANDLE WITH CARE TO PREVENT ACID SPILLAGE**
- LONG SHELF LIFE**
No need to be recharged while stocked (if not activated).
- INTERNAL GAS EMISSION THROUGH VENTING HOLE**
- WIDE VARIETY OF 6V & 12V MODELS**

MOUNTING ANGLE

Diagram illustrating the mounting angle of the battery, showing it can be mounted at 0°.

UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-