

## BB16L-B

BS CODE: 310578

VOLTAGE **12V**

CCA **215A**

CAPACITY 20HR **20.0Ah**

CAPACITY 10HR **19.0Ah**



### DIMENSIONS

<b>LENGTH</b>	175 ±2mm	6.89 ±0.08inch
<b>WIDTH</b>	100 ±2mm	3.94 ±0.08inch
<b>TOTAL HEIGHT</b>	155 ±2mm	6.1 ±0.08inch
<b>WEIGHT</b>	4.43 kg ±5%	9.77 lbs ±5%

Technical drawings showing front, side, and top views of the battery with dimensions in millimeters:

- Front view: 141.8 ±0.5, 175 ±2, 185 ±2
- Side view: 155 ±2, 100 ±2
- Top view: 141.8 ±0.5, 175 ±2, 185 ±2, 34.2 ±0.5

### TERMINAL (mm)

<b>POLARITY</b>	
-----------------	--

Terminal diagrams showing front, side, and top views with dimensions in millimeters:

- Front view: 14.2, 8.2,  $\phi 6.4$
- Side view: 4
- Top view: 8, 12.5

### DRY FEATURES

- TO BE ACTIVATED**  
DRY-charged technology.
- ACID PACK INCLUDED**  
For initial filling.
- PERIODIC MAINTENANCE**  
Refilled with water if necessary.
- HANDLE WITH CARE TO PREVENT ACID SPILLAGE**
- LONG SHELF LIFE**  
No need to be recharged while stocked (if not activated).
- INTERNAL GAS EMISSION THROUGH VENTING HOLE**
- WIDE VARIETY OF 6V & 12V MODELS**

### MOUNTING ANGLE

Diagram showing the battery can be mounted at a 0-degree angle.

### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	-