

BGZ20HL

BS CODE: **300939**

VOLTAGE **12V**

CCA **360A**

CAPACITY 20HR **21.1Ah**

CAPACITY 10HR **20.0Ah**



DIMENSIONS		
LENGTH	176 ±2mm	6.93 ±0.08inch
WIDTH	89 ±2mm	3.5 ±0.08inch
TOTAL HEIGHT	154 ±2mm	6.06 ±0.08inch
WEIGHT	6.96 kg ±5%	15.34 lbs ±5%

TERMINAL (mm)	
POLARITY	
FRONT	SIDE
FRONT	SIDE
TOP	TOP
LEFT TERMINAL	RIGHT TERMINAL

SLA MAX FEATURES	
	FACTORY ACTIVATED AGM (Absorbent Glass Mat) technology.
	READY TO USE Just plug & play.
	NO MAINTENANCE VRLA (Valve Regulated Lead Acid) design.
	SPILL-PROOF DESIGN Factory sealed & electrolyte held in a glass fiber mat.
	NO ACID HANDLING Very safe.
	EXTREME VIBRATION RESISTANCE Reinforced battery case.
	MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE 20% higher than SLA CCA.
	SUPERIOR CAPACITY 20% higher than SLA capacity.

MOUNTING ANGLE	

UPGRADE FOR			
SLA MAX	SLA	MF	DRY
-	BTX20HL	BTX20L-BS BTX20HL-BS	BB18L-A