

BTX14AH

BS CODE: **300863**

VOLTAGE **12V**

CCA **240A**

CAPACITY 20HR **13.7Ah**

CAPACITY 10HR **13.0Ah**



DIMENSIONS

LENGTH	134 ±2mm	5.28 ±0.08inch
WIDTH	89 ±2mm	3.5 ±0.08inch
TOTAL HEIGHT	164 ±2mm	6.46 ±0.08inch
WEIGHT	5.3 kg ±5%	11.68 lbs ±5%

TERMINAL (mm)

POLARITY			
FRONT	SIDE	FRONT	SIDE
		LEFT TERMINAL TOP RIGHT TERMINAL	
TOP	TOP		

SLA MAX FEATURES

- FACTORY ACTIVATED**
AGM (Absorbent Glass Mat) technology.
- READY TO USE**
Just plug & play.
- NO MAINTENANCE**
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**
Very safe.
- EXTREME VIBRATION RESISTANCE**
Reinforced battery case.
- MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE**
20% higher than SLA CCA.
- SUPERIOR CAPACITY**
20% higher than SLA capacity.

MOUNTING ANGLE

UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	BTX14AH/ BB14-A2/B2	BTX14AH-BS	BB14-A2/12N14-4A BB14-B2