

## GR26-620

BS CODE: 300692

VOLTAGE **12V**

CCA\* **570A** — CA\*\* **620A**

CAPACITY 20HR **53Ah**

CAPACITY 10HR **51Ah**



DIMENSIONS		
LENGTH	220 ±2mm	7,72 ±0.08inch
WIDTH	172 ±2mm	6,77 ±0.08inch
TOTAL HEIGHT	199 ±2mm	7,83 ±0.08inch
WEIGHT	15,6 kg ±5%	34,39 lbs ±5%

TERMINAL (mm)	
POLARITY	
FRONT	
FRONT	
TOP	

### SLA MAX FEATURES

- FACTORY ACTIVATED**  
AGM (Absorbent Glass Mat) technology.
- READY TO USE**  
Just plug & play.
- NO MAINTENANCE**  
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**  
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**  
Very safe.
- EXTREME VIBRATION RESISTANCE**  
Reinforced battery case.
- MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE**  
Made to withstand extreme external conditions.
- SUPERIOR CAPACITY**  
15% higher than the flooded battery capacity.

### MOUNTING ANGLE

### REPLACEMENT FOR

POLARIS: 4014132-P  
4081855

\* CCA: COLD CRANKING AMPS, a rating that is used to define the battery's ability to start an engine under low-temperature conditions 0°F.  
\*\* CA: CRANKING AMPS, a rating that is used to define the battery's ability to start an engine at 32°F.