

# 12N5.5-4A/4B

BS CODE: **300841**

VOLTAGE **12V**

CCA **70A**

CAPACITY 20HR **5.8Ah**

CAPACITY 10HR **5.5Ah**



### DIMENSIONS

<b>LENGTH</b>	135 ±2mm	5.31 ±0.08inch
<b>WIDTH</b>	60 ±2mm	2.36 ±0.08inch
<b>TOTAL HEIGHT</b>	130 ±2mm	5.12 ±0.08inch
<b>WEIGHT</b>	2.1 kg ±5%	4.63 lbs ±5%

### TERMINAL (mm)

<b>POLARITY</b>		
<b>FRONT</b>		
<b>SIDE</b>		

### SLA FEATURES

- FACTORY ACTIVATED**  
AGM (Absorbent Glass Mat) technology.
- READY TO USE**  
Just plug & play.
- NO MAINTENANCE**  
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**  
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**  
Very safe.
- HIGH STARTING POWER & EXTENDED CYCLE LIFE**

### MOUNTING ANGLE

### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	12N5.5-4A 12N5.5-4B