

## BB16CL-B

BS CODE: 300771

VOLTAGE **12V**

CCA **230A**

CAPACITY 20HR **20.0Ah**

CAPACITY 10HR **19.0Ah**



DIMENSIONS		
LENGTH	175 ±2mm	6.89 ±0.08inch
WIDTH	100 ±2mm	3.94 ±0.08inch
TOTAL HEIGHT	175 ±2mm	6.89 ±0.08inch
WEIGHT	6.48 kg ±5%	14.29 lbs ±5%

  

TERMINAL (mm)	
POLARITY	

SLA FEATURES	
	<b>FACTORY ACTIVATED</b> AGM (Absorbent Glass Mat) technology.
	<b>READY TO USE</b> Just plug & play.
	<b>NO MAINTENANCE</b> VRLA (Valve Regulated Lead Acid) design.
	<b>SPILL-PROOF DESIGN</b> Factory sealed & electrolyte held in a glass fiber mat.
	<b>NO ACID HANDLING</b> Very safe.
	<b>HIGH STARTING POWER &amp; EXTENDED CYCLE LIFE</b>

MOUNTING ANGLE	

UPGRADE FOR			
SLA MAX	SLA	MF	DRY
-	-	BTX20HL-BS-PW	BB16CL-B