

## BB5L-B

BS CODE: 300671

VOLTAGE **12V**

CCA **65A**

CAPACITY 20HR **5.3Ah**

CAPACITY 10HR **5.0Ah**



### DIMENSIONS

<b>LENGTH</b>	120 ±2mm	4.72 ±0.08inch
<b>WIDTH</b>	60 ±2mm	2.36 ±0.08inch
<b>TOTAL HEIGHT</b>	130 ±2mm	5.12 ±0.08inch
<b>WEIGHT</b>	1.9 kg ±5%	4.19 lbs ±5%

### TERMINAL (mm)

<b>POLARITY</b>		
<b>FRONT</b>	<b>SIDE</b>	<b>TOP</b>

### SLA FEATURES

- FACTORY ACTIVATED**  
AGM (Absorbent Glass Mat) technology.
- READY TO USE**  
Just plug & play.
- NO MAINTENANCE**  
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**  
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**  
Very safe.
- HIGH STARTING POWER & EXTENDED CYCLE LIFE**

### MOUNTING ANGLE

### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	-	BB5L-B/12N5-3B