

## BTX14AH/BB14-A2/B2

BS CODE: **300758**

VOLTAGE **12V**

CCA **210A**

CAPACITY 20HR **14.7Ah**

CAPACITY 10HR **14.0Ah**



### DIMENSIONS

<b>LENGTH</b>	133 ±2mm	5.24 ±0.08inch
<b>WIDTH</b>	90 ±2mm	3.54 ±0.08inch
<b>TOTAL HEIGHT</b>	164 ±2mm	6.46 ±0.08inch
<b>WEIGHT</b>	4.4 kg ±5%	9.7 lbs ±5%

### TERMINAL (mm)

<b>POLARITY</b>		
FRONT	SIDE	TOP

### SLA FEATURES

- FACTORY ACTIVATED**  
AGM (Absorbent Glass Mat) technology.
- READY TO USE**  
Just plug & play.
- NO MAINTENANCE**  
VRLA (Valve Regulated Lead Acid) design.
- SPILL-PROOF DESIGN**  
Factory sealed & electrolyte held in a glass fiber mat.
- NO ACID HANDLING**  
Very safe.
- HIGH STARTING POWER & EXTENDED CYCLE LIFE**

### MOUNTING ANGLE

### UPGRADE FOR

SLA MAX	SLA	MF	DRY
-	-	BTX14AH-BS	BB14-A2/12N14-4A BB14-B2